



# NEW SuperFast Thermopen<sup>®</sup> 4

## Product Features

### CASE/HOUSING

Improved ergonomic design fits your hand better.

Biomaster anti-bacterial additive in casing inhibits bacterial growth.

Available in 10 vibrant colours

Improved water resistance (now waterproof to IP66/67).

Battery cover now includes a screw fitting, even more secure.

Indentation makes it easier to grab the probe.

### INTELLIGENT BACKLIGHT

Automatically activates in low light conditions.

Now 30% brighter.

Turn on by touching the sensor window

### IMPROVED DISPLAY

Motion sensor saves battery life when put down, wakes up when picked up.

Turns on when you open the probe. Still no buttons.

Patented, automatic 360° rotating display can be used in any position, in either hand.

### NEW BATTERY COMPARTMENT

Buttons change °C or °F, 1° or 0.1°, display rotation & sleep settings.

Standard AAA battery.

Battery life extended up to 3,000 hours.

Accurate to  $\pm 0.4$  °C in just 3 seconds.

range	-49.9 to 299.9 °C
resolution	0.1 °C or 1 °C - user selectable
accuracy	$\pm 0.4$ °C (-49.9 to 199.9 °C) otherwise $\pm 1$ °C
units	°C/°F switchable - user selectable
response time	3 seconds (reads to within 1 °C of final temperature of an ice bath in 3 seconds)
battery & life	1 x 1.5 volt AAA - 3000 hours (normal use, without backlight)
sleep mode	10 to 180 seconds - user selectable
sensor type	K thermocouple
water resistance	IP66/67
display	15 mm (horizontal) & 11mm (vertical)
dimensions	19 x 50 x 157 mm
probe	$\varnothing 3.3$ x 110 mm fast response with reduced tip
weight	120 grams

includes FREE traceable certificate of calibration